

Saba Lighting LLB25

IP65



Vaportite



FEATURES

LISTING

- ETL listed for wet locations IP65

FINISH

- UV stabilized powder coated white finish
- 6063 aluminum alloy housing used with high thermostability, high anti-impact strength and good toughness.

HOUSING

- The cover and outer housing are sealed with high elasticity rubber and water-proof silicone rubber.
- No mercury allowing for non-hazardous waste materials

SPECIFICATIONS

Model No.	LLB25					
System Watts	30	40	50	60	80	100
Lumen Output	120-130lm/w					
Color Temp (T)	50=5000K(Std) 40=4000K* 30=3000K*					
Input Voltage (V)	A = 120~277V AD = Dimming 120~277V					
CRI	80+					
Operating Temp	-40°C - 60°C					
Dimensions	3.5"W x 2.75"H x 36"L	3.5"W x 2.75"H x 48"L	3.5"W x 2.75"H x 60"L	3.5"W x 2.75"H x 72"L	3.5"W x 2.75"H x 96"L	
SKU	LLB25-30V-T	LLB25-40V-T	LLB25-50V-T	LLB25-60V-T	LLB25-80V-T	LLB25-100V-T

INSTALLATION

Ceiling Mounting



Suspended Mounting

