

Saba Lighting

AR450-60w-90w-150w



IP65



FEATURES

LISTING

- UL listed for wet locations

HOUSING

- Heavy-gauge, die-cast aluminum housing
- Integral structural support plate for mounting arm ensures strength

FINISH

- Corrosion resistant finish (custom colors available)

LENS

- Heat and impact resistant sealed PC lens around optics
- High output SMD 3030 LED's with PC lens optics

OPTIONS

- Optional Kelvin color*
- Suggest the optional 20kV surge protector to protect your investment

The AR450 combines classic form and versatility to make it an excellent choice for new construction or retrofit application. This fixture is offered in a variety of wattages and mounting options to provide maximum flexibility in all types of applications.

Choose MOUNT



Trunnion
SKU: TR



Slip Fitter
SKU: SF



Pole Mount
SKU: PM

Optics

Std: T3

Optional:

90°=AR-O90

60°=AR-O60

40°=AR-O40

Optional Add-Ons



NEMA Photo Control
SKU: PC-N277
PC-N480

SPECIFICATIONS

| Model No. | AR450 | | |
|----------------|---------------------------|--------------------|--|
| System Watts | 60 | 90 | 150 |
| Lumen Output | 7,800lm | 11,700lm | 19,500lm |
| Color Temp (T) | 50=5000K(Std) 40=4000K* | | |
| Input Voltage | A = 120~277V B = 347~480V | | |
| CRI | 70+ | | |
| Operating Temp | -40°C - 45°C | | |
| MH Equivalent | 200W MH | 300W MH | 500W MH |
| SKU | AR450-T70-60A-T3-M | AR450-T70-90A-T3-M | AR450-T70-150A-T3-M AR450-T70-150B-T3-M |

DIMENSIONS

