

Saba Lighting CY100

IP65



FEATURES

LISTING

- ETL listed for wet locations

HOUSING

- Solid construction die-cast aluminum body.
Finish - Bronze
- Recessed or shoebox installation available.

FINISH

- UV stabilized powder coated finish

LENS

- Unique quick mount design

OPTIONS

- Optional Kelvin color* with adder
- Color option with adder

This canopy light has a slim and low profile design which provides sage and a visually appealing lighting experience. Luminaire can be mounted directly to the ceiling also 3/4" pendant mounting option is available. Quick mount structure for contractors work safely and easily in the confined-space areas.

Optional Add-Ons



Button Photo Control
SKU: PC-B120 (120V)
PC- B277 (277V)



Motion Sensor
SKU: MS

SPECIFICATIONS

| Model No. | CY100 | |
|----------------|---|-----------------|
| System Watts | 45 | 70 |
| Lumen Output | 4793lm - 5001lm | 7386lm - 7645lm |
| Color Temp (T) | 50=5000K(Std) 30=3000K*, 40=4000K* | |
| Input Voltage | A = 120~277V AD = Dimming 120~277V B = 347~480V BD = Dimming 347~480V | |
| CRI | 70+ | |
| Operating Temp | -40°C - 55°C | |
| MH Equivalent | 150W MH | 250W MH |
| SKU | CY100-T70-45V | CY100-T70-70V |

DIMENSIONS

